Product Information Sheet




BEDROCK

Floor Sealer: Base Coat for Vinyl & Terrazzo



Product

- ✓ Assists to level out undulating floor surfaces
- ✓ Provides a barrier that resists stains, water and detergents spills
- ✓ Improves wearability and life of top coat
- ✓ Ready to use





Colour	Milky white
Odour	Polymer odour
pH	8.50 – 9.50
Solids (%)	18.00
Coverage (m ² /Lit)	40- 50 m ² /L (Typical)

Product Code		Outer Pack	APN
CHRC-610015A	(5L)	3	9324828001416
CHRC-61015	(15L)	1	9324828001423

Application

Task	Method
Floor Preparation	1. Strip off old sealers or finishes with STEAMROLLER II, MELTDOWN or SLEDGEHAMMER as directed.
	2. Rinse well with warm water and allow it to dry.
	3. Dust mop entire area.
Application	1. Apply a thin even coat of BEDROCK using an Oates Poly-cotton mop (MH-PR-24) or a Nylon Polish
	Spreader (SM-156).
	2. Allow coating time to completely dry (approximately 45 minutes).
	3. Apply a second coat (if necessary) or apply the chosen floor finish (2 or 3 coats) after BEDROCK is dried.
	Do not buff BEDROCK or leave it as a finishing coat - it is a non-buffable sealer.

Hazard Statement

H316: Causes mild skin irritation.

Prevention

P102: Keep out of reach of children.

P264: Wash affected areas thoroughly after handling.

P280: Wear protective gloves, protective clothing and eye or face protection.

Version: 1 Page 1 of 1

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.



Steamaster Pty Ltd

Tel: 1300 855 677 | Tel: +61 2 9796 3433 | Fax: +61 2 9796 3395 Email: sales@steamaster.com.au | Website: www.steamaster.com.au