

# SAFESTEP LIQUID

## Liquid Wax Maintainer

## Product

- ✓ Maintains the natural look of timber by filling and feeding the timber grain
- ✓ Non-flammable and no harsh odour
- ✓ Shaking the product makes it thinner and easy to apply
- ✓ Protects, enhances and beautifies timber flooring



Crème liquid spirit wax maintainer is for timber floors sealed with solvent based finishes which have already been applied with SAFESTEP PASTE. Perfect for maintaining originally and antique appearance of old timber floors. Product can be easily adjusted for slip resistance. It can be thinned down with either mineral turps or white spirits. In cold weather simply add a small amount of turpentine or white spirit to thin product down further. Thicker applications give less gloss and greater slip resistance in walkways and flooring,

## Technical

Colour	White
Odour	Solvent
pH	N/A

Product Code	Outer Pack	APN
CHRC-660015A (5L)	3	932482800262

## Application

Task	Method
Preparation	<ol style="list-style-type: none"><li>1. If required, strip off old wax finish using SAFE DE-WAX as directed.</li><li>2. Let the floor dry. DO NOT rinse with water.</li></ol>
Polish application	<ol style="list-style-type: none"><li>1. Once the floor is dry apply a thin layer of SAFESTEP PASTE with a lambswool polish applicator or Oates Poly-cotton mop.</li><li>2. If coat is uneven, buff surface with a red or coral pad whilst still wet.</li><li>3. Recoat if floor still looks dry.</li></ol>
Maintenance	<ol style="list-style-type: none"><li>1. Dust mop daily to remove sand and grit tracked over the floor and where possible use carpet matting in entrance ways.</li><li>2. Apply 2 coats of SAFESTEP LIQUID using an Oates Poly-cotton mop to floors previously finished with SAFESTEP PASTE to fill grain and maintain a warm even gloss.</li></ol>

**Note:** Thicker coats will increase slip resistance, therefore caution should be taken when applying coats to timber dance floors

### Hazard Statement

- H341: Suspected of causing genetic defects.
- H351: Suspected of causing cancer.
- AUH066: Repeated exposure may cause skin dryness or cracking.

# SAFESTEP LIQUID

## Liquid Wax Maintainer

### Prevention

- P102: Keep out of reach of children.
- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P261: Avoid breathing fumes, mists, vapours or spray.
- P264: Wash contacted areas thoroughly after handling.
- P271: Use only in a well ventilated area.
- P281: Use personal protective equipment as required.